

# 2SC3831

**Silicon NPN Triple Diffused Planar Transistor (High Voltage and High Speed Switching Transistor)**

**Application : Switching Regulator and General Purpose**

**Absolute maximum ratings (Ta=25°C)**

Symbol	2SC3831	Unit
V <sub>CB0</sub>	600	V
V <sub>CE0</sub>	500	V
V <sub>EB0</sub>	10	V
I <sub>c</sub>	10(Pulse20)	A
I <sub>B</sub>	4	A
P <sub>c</sub>	100(Tc=25°C)	W
T <sub>J</sub>	150	°C
T <sub>stg</sub>	-55 to +150	°C


**Electrical Characteristics (Ta=25°C)**

Symbol	Conditions	2SC3831	Unit
I <sub>CB0</sub>	V <sub>CB</sub> =600V	1max	mA
I <sub>EB0</sub>	V <sub>EB</sub> =10V	100max	μA
V <sub>(BR)CEO</sub>	I <sub>c</sub> =25mA	500min	V
h <sub>FE</sub>	V <sub>CE</sub> =4V, I <sub>c</sub> =5A	10to30	
V <sub>CE(sat)</sub>	I <sub>c</sub> =5A, I <sub>B</sub> =1A	0.5max	V
V <sub>BE(sat)</sub>	I <sub>c</sub> =5A, I <sub>B</sub> =1A	1.3 max	V
f <sub>r</sub>	V <sub>CE</sub> =12V, I <sub>E</sub> =-1A	8typ	MHZ
COB	V <sub>CB</sub> =10V, f=1MHZ	105typ	pF


**Typical Switching Characteristics (Common Emitter)**

V <sub>CC</sub> (V)	R <sub>L</sub> (Ω)	I <sub>c</sub> (A)	V <sub>BB1</sub> (V)	V <sub>BB2</sub> (V)	I <sub>B1</sub> (A)	I <sub>B2</sub> (A)	t <sub>on</sub> (μs)	t <sub>stg</sub> (μs)	t <sub>f</sub> (μs)
200	40	5	10	-5	0.5	-1.0	1max	4.5max	0.5max


**External Dimensions MT-100(TO3P)**




**I<sub>c</sub>-V<sub>CE</sub> Characteristics (Typical)**




**V<sub>CE(sat)</sub>, V<sub>BE(sat)</sub>-I<sub>c</sub> Temperature Characteristics (Typical)**




**I<sub>c</sub>-V<sub>BE</sub> Temperature Characteristics (Typical)**




**h<sub>FE</sub>-I<sub>c</sub> Characteristics (Typical)**




**t<sub>on</sub>\*t<sub>stg</sub>\*t<sub>f</sub>-I<sub>c</sub> Characteristics (Typical)**




**θ<sub>j-a</sub>-t Characteristics**



**Safe Operating Area (Single Pulse)**



**Reverse Bias Safe Operating Area**



**P<sub>c</sub>-T<sub>a</sub> Derating**

