

### DESCRIPTION

M54563FP is an eight-circuit output-sourcing Darlington transistor array. The circuits are made of PNP and NPN transistors. This semiconductor integrated circuit performs high-current driving with extremely low input-current supply.

### FEATURES

- High breakdown voltage ( $BV_{CEO} \geq 50V$ )
- High-current driving ( $I_o(max) = -500mA$ )
- With clamping diodes
- Driving available with PMOS IC output of 6 ~ 16V or with TTL output
- Wide operating temperature range ( $T_a = -20$  to  $+75^\circ C$ )
- Output current-sourcing type

### APPLICATION

Drives of relays, printers, LEDs, fluorescent display tubes and lamps, and interfaces between MOS-bipolar logic systems and relays, solenoids, or small motors


### FUNCTION

The M54563P and M54563FP each have eight circuits, which are made of input inverters and current-sourcing outputs. The outputs are made of PNP transistors and NPN Darlington transistors. The PNP transistor base current is constant. A clamping diode is provided between each output and GND.  $V_s$  and GND are used commonly among the eight circuits.


The inputs have resistance of  $3k\Omega$ , and voltage of up to 10V is applicable. Output current is 500 mA maximum. Supply voltage  $V_s$  is 50V maximum.

The M54563FP is enclosed in a molded small flat package, enabling space-saving design.

### PIN CONFIGURATION




Package type 18P4G(P)



Package type 20P2N-A(FP)

NC : No connection

### CIRCUIT DIAGRAM



The eight circuits share the  $V_s$  and GND.

The diode, indicated with the dotted line, is parasitic, and cannot be used.

Unit :  $\Omega$

8-UNIT 500mA SOURCE TYPE DARLINGTON TRANSISTOR ARRAY WITH CLAMP DIODE

**ABSOLUTE MAXIMUM RATINGS** (Unless otherwise noted, Ta = -20 ~ +75°C)

| Symbol             | Parameter                      | Conditions                       | Ratings          | Unit |
|--------------------|--------------------------------|----------------------------------|------------------|------|
| V <sub>CEO</sub> # | Collector-emitter voltage      | Output, L                        | -0.5 ~ +50       | V    |
| V <sub>S</sub>     | Supply voltage                 |                                  | 50               | V    |
| V <sub>I</sub>     | Input voltage                  |                                  | -0.5 ~ +10       | V    |
| I <sub>O</sub>     | Output current                 | Current per circuit output, H    | -500             | mA   |
| I <sub>F</sub>     | Clamping diode forward current |                                  | -500             | mA   |
| V <sub>R</sub> #   | Clamping diode reverse voltage |                                  | 50               | V    |
| P <sub>d</sub>     | Power dissipation              | Ta = 25°C, when mounted on board | 1.79(P)/1.10(FP) | W    |
| T <sub>opr</sub>   | Operating temperature          |                                  | -20 ~ +75        | °C   |
| T <sub>stg</sub>   | Storage temperature            |                                  | -55 ~ +125       | °C   |

# : Unused I/O pins must be connected to GND.

**RECOMMENDED OPERATING CONDITIONS** (Unless otherwise noted, Ta = -20 ~ +75°C)

| Symbol          | Parameter  | Limits  |     |     | Unit |    |
|-----------------|--|---|-----|-----|------|----|
|                 |  | min   | typ | max |      |    |
| V <sub>S</sub>  | Supply voltage   | 0   | —   | 50  | V    |    |
| I <sub>O</sub>  | Output current<br>(Current per 1 circuit when 8 circuits are coming on simultaneously) | Duty Cycle<br>P : no more than 8%<br>FP : no more than 5%   | 0   | —   | -350 | mA |
|                 |  | Duty Cycle<br>P : no more than 55%<br>FP : no more than 30% | 0   | —   | -100 |    |
| V <sub>IH</sub> | "H" input voltage  | 2.4   | —   | 10  | V    |    |
| V <sub>IL</sub> | "L" input voltage  | 0   | —   | 0.2 | V    |    |

**ELECTRICAL CHARACTERISTICS** (Unless otherwise noted, Ta = -20 ~ +75°C)

| Symbol                  | Parameter                            | Test conditions  | Limits |      |      | Unit |
|-------------------------|--------------------------------------|--|--------|------|------|------|
|                         |                                      |  | min    | typ* | max  |      |
| I <sub>S (leak)</sub> # | Supply leak current                  | V <sub>S</sub> = 50V, V <sub>I</sub> = 0.2V                          | —      | —    | 100  | μA   |
| V <sub>CE (sat)</sub>   | Collector-emitter saturation voltage | V <sub>S</sub> = 10V, V <sub>I</sub> = 2.4V, I <sub>O</sub> = -350mA | —      | 1.6  | 2.4  | V    |
|                         |                                      | V <sub>S</sub> = 10V, V <sub>I</sub> = 2.4V, I <sub>O</sub> = -100mA | —      | 1.45 | 2.0  |      |
| I <sub>I</sub>          | Input current                        | V <sub>I</sub> = 3V  | —      | 0.6  | 1.0  | mA   |
|                         |                                      | V <sub>I</sub> = 10V   | —      | 2.9  | 5.0  |      |
| I <sub>S</sub>          | Supply current                       | V <sub>S</sub> = 50V, V <sub>I</sub> = 3V (all input)                | —      | 5.6  | 15.0 | mA   |
| V <sub>F</sub>          | Clamping diode forward voltage       | I <sub>F</sub> = -350mA  | —      | -1.2 | -2.4 | V    |
| I <sub>R</sub> #        | Clamping diode reverse current       | V <sub>R</sub> = 50V   | —      | —    | 100  | μA   |

\* : The typical values are those measured under ambient temperature (Ta) of 25°C. There is no guarantee that these values are obtained under any conditions.

# : Unused I/O pins must be connected to GND.

**SWITCHING CHARACTERISTICS** (Unless otherwise noted, Ta = 25°C)


| Symbol           | Parameter     | Test conditions                | Limits |      |     | Unit |
|------------------|---------------|--------------------------------|--------|------|-----|------|
|                  |               |                                | min    | typ  | max |      |
| t <sub>on</sub>  | Turn-on time  | C <sub>L</sub> = 15pF (note 1) | —      | 100  | —   | ns   |
| t <sub>off</sub> | Turn-off time |                                | —      | 4800 | —   | ns   |

# POWEREX

## M54563P/FP


### 8-UNIT 500mA SOURCE TYPE DARLINGTON TRANSISTOR ARRAY WITH CLAMP DIODE

#### NOTE 1 TEST CIRCUIT







- (1) Pulse generator (PG) characteristics : PRR = 1kHz,  $t_w = 10\mu s$ ,  $t_r = 6ns$ ,  $t_f = 6ns$ ,  $Z_o = 50\Omega$ ,  $V_i = 0$  to  $2.4V$
- (2) Input-output conditions :  $R_L = 30\Omega$ ,  $V_s = 10V$
- (3) Electrostatic capacity  $C_L$  includes floating capacitance at connections and input capacitance at probes

#### TIMING DIAGRAM




#### TYPICAL CHARACTERISTICS




8-UNIT 500mA SOURCE TYPE DARLINGTON TRANSISTOR ARRAY WITH CLAMP DIODE


Duty-Cycle-Output Current Characteristics (M54563FP)




Duty-Cycle-Output Current Characteristics (M54563FP)




Grounded Emitter Transfer Characteristics



Clamping Diode Characteristics



Input Characteristics



Input Characteristics

