
Infrared Remote Control Transmitter**PT2248**

Description

PT2248 is an infrared remote control transmitter utilizing CMOS Technology. It is capable of 18 functions and a total of 75 commands. Single-shot and continuous keys are available. Furthermore, multiple keying is possible.

Features

- CMOS Technology
- Low Power Consumption
- Wide Range of Operating Supply Voltage allows Low Voltage Operation ($V_{cc} = 2.2 \sim 5.0 \text{ V}$)
- Multiple Keying is Possible (Maximum of 6 Keys)
- Less External Components
- An Oscillator can be constructed by connecting a ceramic resonator at the oscillation circuit

Applications


- Television (TV) Remote Control Transmitter
- Video Cassette Recorder (VCR) Remote Control Transmitter

Infrared Remote Control Transmitter


PT2248

Pin Configuration

PT2248




Block Diagram



Infrared Remote Control Transmitter

PT2248

Application Circuit



- Notes:
1. R = 200 Ohms to 3.9 K Ohms
 2. It is highly recommended that the 47µf capacitor be situated near the Vcc.

Infrared Remote Control Transmitter

PT2248

Order Information

PART NUMBER	PACKAGE
PT2248	16 Pins, DIP
PT2248-S	16 Pins, SO
PT2248-SN	16 Pins, SO (Narrow)

PT 2248 - X

