


ST 2SA1266

PNP Silicon Epitaxial Planar Transistor

for switching and AF amplifier applications.

The transistor is subdivided into three groups, O, Y and G according to its DC current gain.

On special request, these transistors can be manufactured in different pin configurations.



1. Emitter 2. Collector 3. Base


TO-92 Plastic Package

Weight approx. 0.19g

Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)


	Symbol	Value	Unit
Collector Base Voltage	$-V_{CBO}$	50	V
Collector Emitter Voltage	$-V_{CEO}$	50	V
Emitter Base Voltage	$-V_{EBO}$	5	V
Collector Current	$-I_C$	150	mA
Base Current	$-I_B$	50	mA
Power Dissipation	P_{tot}	500	mW
Junction Temperature	T_j	125	$^\circ\text{C}$
Storage Temperature Range	T_s	-55 to +125	$^\circ\text{C}$

G S P FORM A IS AVAILABLE



SEMTECH ELECTRONICS LTD.

(Subsidiary of Semtech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)



ISO/TS 16949 : 2002
Certificate No. 05103



ISO 14001
Certificate No. 7116



ISO 9001 : 2000
Certificate No. 0508-1999-01-002-001


Dated : 07/12/2002

ST 2SA1266

Characteristics at $T_{amb}=25\text{ }^{\circ}\text{C}$


	Symbol	Min.	Typ.	Max.	Unit	
DC Current Gain at $-V_{CE}=6\text{V}$, $-I_C=2\text{mA}$	Current Gain Group O Y G	h_{FE}	70	-	140	-
		h_{FE}	120	-	240	-
		h_{FE}	200	-	400	-
		h_{FE}	25	-	-	-
at $-V_{CE}=6\text{V}$, $-I_C=150\text{mA}$						
Collector Cutoff Current at $-V_{CB}=50\text{V}$	$-I_{CBO}$	-	-	0.1	μA	
Emitter Cutoff Current at $-V_{EB}=5\text{V}$	$-I_{EBO}$	-	-	0.1	μA	
Collector Emitter Saturation Voltage at $-I_C=100\text{mA}$, $-I_B=10\text{mA}$	$-V_{CE(sat)}$	-	0.1	0.3	V	
Base Emitter Saturation Voltage at $-I_C=100\text{mA}$, $-I_B=10\text{mA}$	$-V_{BE(sat)}$	-	-	1.1	V	
Transition Frequency at $-V_{CE}=10\text{V}$, $-I_E=1\text{mA}$	f_T	80	-	-	MHz	
Noise Figure at $-V_{CE}=6\text{V}$, $-I_C=0.1\text{V}$, $f=1\text{KHZ}$, $R_G=10\text{k}\Omega$	NF	-	1	10	dB	
Collector Output Capacitance at $-V_{CB}=10\text{V}$, $f=1\text{MHz}$	C_{OB}	-	4	7	pF	

G S P FORM A IS AVAILABLE



SEMTECH ELECTRONICS LTD.

(Subsidiary of Semtech International Holdings Limited, acompany listed on the Hong Kong Stock Exchange, Stock Code: 724)



Dated : 07/12/2002