


MCR100-3 ... MCR100-8



1. Cathode 2. Gate 3. Anode


TO-92 Plastic Package
Weight approx. 0.19g

MAXIMUM RATINGS ($T_J=25^\circ\text{C}$ unless otherwise noted.)

Rating	Symbol	Value	Unit
Peak Repetitive Forward and Reverse Blocking Voltage, Note 1 ($T_J=25$ to 125°C , $R_{GK}=1\text{K}\Omega$)	V_{DRM} and V_{RRM}	100 200 300 400 500 600	Volts
Forward Current RMS (All Conduction Angles)	$I_{T(RMS)}$	0.8	Amps
Peak Forward Surge Current, $T_A=25^\circ\text{C}$ (1/2 Cycle, Sine Wave, 60Hz)	I_{TSM}	10	Amps
Circuit Fusing ($t=8.3\text{ms}$)	I^2t	0.415	A^2s
Peak Gate Power - Forward, $T_A=25^\circ\text{C}$	P_{GM}	0.1	Watts
Average Gate Power - Forward, $T_A=25^\circ\text{C}$	$P_{GF(AV)}$	0.01	Watt
Peak Gate Current - Forward, $T_A=25^\circ\text{C}$ ($300\mu\text{s}, 120\text{PPS}$)	I_{GFM}	1	Amp
Peak Gate Voltage - Reverse	V_{GRM}	5	Volts
Operating Junction Temperature Range @ Rated V_{RRM} and V_{DRM}	T_J	-40 to +125	°C
Storage Temperature Range	T_s	-40 to +150	°C

Note 1. Ratings apply for zero or negative gate voltage; however, positive gate voltage shall not be applied concurrent with negative potential on the anode.

GSP FORM A IS AVAILABLE



РАДИОТЕХ-ТРЕЙД

Тел.: (495) 795-0805
Факс: (495) 234-1603
Эл. почта: info@rct.ru
Веб: www.rct.ru


MCR100-3 ... MCR100-8

CHARACTERISTICS ($T_c=25^\circ\text{C}$, $R_{GK}=1\text{K}\Omega$ unless otherwise noted.)

Characteristic	Symbol	Min	Max	Unit
Peak Forward or Reverse Blocking Current (V_{AK} =Rated V_{DRM} or V_{RRM})	I_{DRM}, I_{RRM}	-	10	μA
Forward "On" Voltage ($I_{TM}=1\text{A}$ Peak @ $T_A=25^\circ\text{C}$)	V_{TM}	-	1.7	Volts
Gate Trigger Current(Continuous dc),Note 1 (Anode Voltage=7Vdc, $R_L=100$ Ohms)	I_{GT}	-	200	μA
Gate Trigger Voltage(Continuous dc) (Anode Voltage=7Vdc, $R_L=100$ Ohms) (Anode Voltage=Rated V_{DRM} , $R_L=100$ Ohms)	V_{GT}	-	0.8	Volts
Holding Current (Anode Voltage=7Vdc,initiating current=20mA)	I_H	-	5	mA


Note 1. R_{GK} current is not included in measurement.

GSP FORM A IS AVAILABLE



SEMTECH ELECTRONICS LTD.

(Subsidiary of Semtech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)



ISO/TS 16949 : 2002
Certificate No. 05103



ISO 14001
Certificate No. 7116



ISO 9001 : 2000
Certified No. 554-199-007-04

Dated : 06/12/2003

MCR100-3 ... MCR100-8




Figure 1. Typical Gate Trigger Current Versus Junction Temperature




Figure 2. Typical Gate Trigger Voltage Versus Junction Temperature




Figure 3. Typical Holding Current Versus Junction Temperature




Figure 4. Typical Latching Current Versus Junction Temperature




Figure 5. Typical RMS Current Derating





Figure 6. Typical On-State Characteristics



SEMTECH ELECTRONICS LTD.

(Subsidiary of Semtech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)



ISO/TS 16949 : 2002
Certificate No. 05103



ISO 14001
Certificate No. 7116



ISO 9001 : 2000
Certificate No. 554-1994-BR-001

Dated : 06/12/2003