


ERSA VAC 2/3/5

VAC 2 / 3 / 5



VAC 22



VAC 32



VAC 52



Antistatic standard solder suckers

Outstanding features of the ERSA VAC 2, ERSA VAC 3 and ERSA VAC 5 solder suckers are the high pumping performance and low backlash desoldering properties. The antistatic construction allows carefree desoldering of electrostatically irritable assemblies. The double-gasket system ensures constant pumping performance. The long, slim desoldering tips also allow work on closely assembled boards.

Technical data:

VAC 2 solder sucker

Suction capacity: 8.9 cm³ (22.6 in³)

Design: metal, antistatic

VAC 3 solder sucker

Suction capacity: 10 cm³ (25.4 in³)

Design: plastic, antistatic

VAC 5 solder sucker

Suction capacity: 14.5 cm³ (36.8 in³)

Design: plastic, antistatic

Order nos.:


VAC 2 Antistatic solder sucker

VAC 3 Antistatic solder sucker

VAC 5 Antistatic solder sucker


ERSA Soldapullt

US 140 / PT 109



SRT 12 A

US 340 / AS 196



LS 197



High-power industrial solder suckers

All industrially proven Soldapullt systems are characterized by high backlash absorption, outstanding pumping performance and extensive solder compartments. The antistatic types allow carefree desoldering on electrostatically irritable assemblies. After melting the solder with a soldering iron, quick and clean removal is ensured by suction.

Technical data:

US 140 solder sucker

Suction capacity: 19 cm³ (48.3 in³)

Design: plastic

PT 109 solder sucker

Suction capacity: 22 cm³ (55.9 in³)

Design: plastic

AS 196 solder sucker

Suction capacity: 34 cm³ (86.4 in³)

Design: plastic, antistatic

US 340 solder sucker

Suction capacity: 19 cm³ (48.3 in³)

Lift adjustable

Design: plastic, antistatic

Order nos.:

US 140 Solder sucker

PT 109 Solder sucker

AS 196 Antistatic solder sucker

US 340 Antistatic solder sucker