

20 STERN AVE.
SPRINGFIELD, NEW JERSEY 07081
U.S.A.

TELEPHONE: (201) 376-2922
(212) 227-6005
FAX: (201) 376-8960

2N404

JUNCTION TRANSISTOR

Germanium p-n-p Alloy Type

SWITCHING SERVICE

Maximum Ratings, Absolute Values:

COLLECTOR-TO-BASE VOLTAGE	-25 max.	volts
COLLECTOR-TO-EMITTER VOLTAGE	-24 max.	volts
COLLECTOR CURRENT	-100 max.	ma
EMITTER-TO-BASE VOLTAGE	-12 max.	volts
EMITTER CURRENT	100 max.	ma
COLLECTOR DISSIPATION (See Rating Chart):		
At ambient temperature of 25° C. . .	120 max.	mW
At ambient temperature of 55° C. . .	35 max.	mW
At ambient temperature of 71° C. . .	10 max.	mW
AMBIENT TEMPERATURE:		
Operating	85 max.	°C
Storage	-65 to +85	°C

CHARACTERISTICS RANGE VALUES FOR EQUIPMENT DESIGN

Voltage values are given with respect to the base unless otherwise specified. Ambient temperature = 25°C

	Typical	Min.	Max.	
DC Collector Breakdown voltage with dc collector current = -20 μ a, dc emitter current = 0	-40	-25	-	volts
DC Collector Cutoff Current with dc collector voltage = -12 volts, dc emitter current = 0.	-2	-	-5	μ a
DC Collector Cutoff Current with dc collector voltage = -12 volts, dc emitter current = 0 and ambient temperature = 80° C .	-45	-	-90	μ a
DC Emitter Breakdown Voltage with dc emitter current = -20 μ a, dc col- lector current = 0 .	-35	-12	-	volts
DC Emitter Cutoff Current with dc emitter voltage = -2.5 volts, dc collector current = 0	-1	-	-2.5	μ a
DC Collector-to- Emitter (Punch- Through) Voltage* . .	-40	-24	-	volts

	Typical	Min.	Max.	
DC Collector-to-Emitter Saturation Voltage with dc collector current = -12 ma, dc base current = -0.4 ma	-0.10	-	-0.15	volt
DC Base-to-Emitter Saturation Voltage with dc collector current = -12 ma, dc base current = -0.4 ma	-0.25	-	-0.35	volt
DC Collector-to-Emitter Saturation Voltage with dc collector current = -24 ma, dc base current = -1 ma	-0.12	-	-0.20	volt
DC Base-to-Emitter Saturation Voltage with dc collector current = -24 ma, dc base current = -1 ma	-0.32	-	-0.40	volt
Stored Base Charge with DC Collector Current = -10 ma, DC Base Current = -1 ma	800	-	1400	$\mu\text{sec/cm}^2$
Alpha-Cutoff Frequency with dc collector voltage = -6 volts, dc emitter current = 1 ma	12	4	-	mc
Collector Capacitance with dc collector voltage = -6 volts, dc emitter current = 0.	12	-	20	μf
Junction Temperature Rise in free air	0.28	-	0.35	$^{\circ}\text{C/mw}$

* The dc collector-to-emitter (punch-through) voltage may be determined by connecting a high-impedance voltmeter (11 megohms or greater) between the emitter and base and measuring the collector-to-base voltage when causes the emitter to assume an emitter-to-base floating voltage of -1 volt. In making this test, care must be taken not to exceed the maximum collector-to-base voltage specified under Maximum Ratings.



Quality Semi-Conductors

