

isc Silicon NPN Power Transistor


BUW12F

DESCRIPTION

- Collector-Emitter Sustaining Voltage-
: $V_{CEO(SUS)} = 400V(\text{Min.})$
- Low Collector Saturation Voltage-
: $V_{CE(sat)} = 1.5V(\text{Max.})@I_C = 6A$
- High Speed Switching

APPLICATIONS

- Designed for high voltage, fast switching industrial applications.




ABSOLUTE MAXIMUM RATINGS ($T_a=25^\circ\text{C}$)

| SYMBOL | PARAMETER | VALUE | UNIT |
|-----------|---|---------|------------------|
| V_{CBO} | Collector-Base Voltage | 850 | V |
| V_{CEO} | Collector-Emitter Voltage | 400 | V |
| V_{EBO} | Emitter-Base Voltage | 9 | V |
| I_C | Collector Current-Continuous | 8 | A |
| I_{CM} | Collector Current-Peak | 20 | A |
| I_B | Base Current | 4 | A |
| I_{BM} | Base Current-Peak | 6 | A |
| P_C | Collector Power Dissipation @ $T_c=25^\circ\text{C}$ | 34 | W |
| T_j | Junction Temperature | 150 | $^\circ\text{C}$ |
| T_{stg} | Storage Temperature Range | -65~150 | $^\circ\text{C}$ |

THERMAL CHARACTERISTICS

| SYMBOL | PARAMETER | MAX | UNIT |
|--------------|--------------------------------------|-----|--------------------|
| R_{th-j-c} | Thermal Resistance, Junction to Case | 3.7 | $^\circ\text{C/W}$ |



isc Silicon NPN Power Transistor**BUW12F****ELECTRICAL CHARACTERISTICS** $T_C=25^{\circ}\text{C}$ unless otherwise specified

| SYMBOL | PARAMETER | CONDITIONS | MIN | TYP. | MAX | UNIT |
|----------------|--------------------------------------|---|-----|------|------------|------|
| $V_{CEO(SUS)}$ | Collector-Emitter Sustaining Voltage | $I_C=0.1\text{A}; I_B=0, L=25\text{mH}$ | 400 | | | V |
| $V_{CE(sat)}$ | Collector-Emitter Saturation Voltage | $I_C=6\text{A}; I_B=1.2\text{A}$ | | | 1.5 | V |
| $V_{BE(sat)}$ | Base-Emitter Saturation Voltage | $I_C=6\text{A}; I_B=1.2\text{A}$ | | | 1.5 | V |
| I_{CES} | Collector Cutoff Current | $V_{CE}=V_{CES}; V_{BE}=0$ $V_{CE}=V_{CES}; V_{BE}=0; T_C=125^{\circ}\text{C}$ | | | 1.0 3.0 | mA |
| I_{EBO} | Emitter Cutoff Current | $V_{EB}=9\text{V}; I_C=0$ | | | 10 | mA |
| h_{FE-1} | DC Current Gain | $I_C=10\text{mA}; V_{CE}=5\text{V}$ | 10 | | 35 | |
| h_{FE-2} | DC Current Gain | $I_C=1\text{A}; V_{CE}=5\text{V}$ | 10 | | 35 | |

Switching Times; Resistive Load

| | | | | | | |
|----------|--------------|---|--|--|-----|---------------|
| t_{on} | Turn-on Time | $I_C=6\text{A}; I_{B1}=-I_{B2}=1.2\text{A}$ | | | 1.0 | μs |
| t_s | Storage Time | | | | 4.0 | μs |
| t_f | Fall Time | | | | 0.8 | μs |